Appendix A

Design Drawings



This page intentionally left blank




PRELIMINARY NOT FOR CONSTRUCTION 07/03/2014

CAMBRIA, CALIFORNIA

EMERGENCY WATER SUPPLY PROJECT

PWC # XXX

90% DESIGN SUBMITTAL JULY 2014



<u>VICINITY MAP</u>



LOCATION MAP

		SHEET INDEX	
SHT NO.	DWG NO.	SHEET TITLE	INCLUDED
1	G-1	TITLE SHEET & SHEET INDEX	Х
2	G-2	GENERAL NOTES & LEGENDS & ABBREVIATIONS	
3	P-1	PROCESS FLOW DIAGRAM	Х
4	C-1	OVERALL SITE PLAN	Х
5	C-2	CONVEYANCE PIPING PLAN	Х
6	C-3	AWTP GRADING AND DRAINAGE PLAN	Х
7	C-4	AWTP YARD PIPING PLAN	Х
8	C-5	BRINE EVAPORATION POND PLAN	Х
9	C-6	BRINE EVAPORATION POND SECTION AND DETAILS I	Χ
10	C-7	BRINE EVAPORATION POND SECTION AND DETAILS II	Χ
11	C-8	CIVIL DETAILS I	Х
12	C-9	CIVIL DETAILS II	Х
13	S-1	AWTP STRUCTURAL GENERAL NOTES	Х
14	S-2	AWTP STRUCTURAL DETAILS	Х
15	M-1	MECHANICAL NOTES, LEGENDS, AND PIPE SCHEDULE	
16	M-2	CONTROL ROOM GENERAL ARRANGEMENT	Х
17	M-3	UF GENERAL ARRANGEMENT	Х
18	M-4	RO TRAIN #1 GENERAL ARRANGEMENT	Х
19	M-5	RO TRAIN #2 GENERAL ARRANGEMENT	Х
20	M-6	THIRD STAGE RO GENERAL ARRANGEMENT (NOT INCLUDED IN THIS SET)	Х
21	M-7	UV GENERAL ARRANGEMENT	Х
22	M-8	CHEMICAL SYSTEM GENERAL ARRANGEMENT	Х
23	E-1	ELECTRICAL NOTES, LEGENDS, AND ABBREVIATIONS 1 OF 2	
24	E-2	ELECTRICAL NOTES, LEGENDS, AND ABBREVIATIONS 2 OF 2	
25	E-3	ELECTRICAL SINGLE LINE DIAGRAM - AWTP	Х
26	E-4	ELECTRICAL POWER AND CONTROL PLAN - AWTP	Х
27	E-5	ELECTRICAL SINGLE LINE DIAGRAM - EVAPORATION POND	Х
28	E-6	ELECTRICAL POWER AND CONTROL PLAN - EVAPORATION POND	Х
29	E-7	ELECTRICAL LIGHTING PANELBOARD AND FIXTURE SCHEDULES 1 OF 2	
30	E-8	ELECTRICAL LIGHTING PANELBOARD AND FIXTURE SCHEDULES 2 OF 2	
31	E-9	ELECTRICAL DETAILS 1 OF 2	
32	E-10	ELECTRICAL DETAILS 1 OF 2	
33	E-11	ELECTRICAL CA TITLE 24 LIGHTING CALCULATION 1	
34	E-12	ELECTRICAL CA TITLE 24 LIGHTING CALCULATION 2	
35	I-1	INSTRUMETATION LEGENDS, SYMBOLS, AND ABBREVIATIONS	Х
36	I-2	OVERALL SYSTEM ARCHITECTURE	Х
37	I-3	P&ID - SUPPLY WELL	Х
38	I-4	P&ID - AWTP INFLUENT TANK AND MF FEED PUMP	X
39	I-5	P&ID - MF CONTAINER	X
40	I-6	P&ID - BREAK/BACKWASH TANK AND MF CIP TANK	X
41	I-7	P&ID - RO FEED SUPPLY PUMPS AND PRIMARY RO TRAINS 1 AND 2	X
42	I-8	P&ID - THIRD STAGE RO	Х
43	1-9	P&ID - UV	X
44	I-10	P&ID - PRODUCT WATER TANK, PUMP STATION AND RIW INJECTION	X
45 46	I-11	P&ID - CHEMICAL SYSTEMS P&ID - BRINE EVAPORATION SYSTEM	X
	I-12	P&ID - BRINE EVAPORATION SYSTEM	Х
H2OI INNO 47	VATION SUPPLY P&IDS	ME FFFD DUMD CIVID DOLD	x
47	O-14024-C01-0290 O-14024-C01-0300	MF FEED PUMP SKID - P&ID MF STRAINER STATION - P&ID	X
48 49			X
49 50	O-14024-C01-0310	MICROFILTRATION UNIT W/ FCV - P&ID	
50 51	O-14024-C01-0360 O-14024-C01-0370	MF BACKPULSE SYSTEM - P&ID MF CIP SYSTEM W/ VFD CONTROLLED PUMP - P&ID	X X
51 52	O-14024-C01-0370	RO FEED PUMP SKID - P&ID	X
53	O-14024-C01-0400 O-14024-C01-0410	PRIMARY RO TRAIN 1 CONTAINER - P&ID	X
53	O-14024-C01-0410	PRIMARY RO TRAIN 1 CONTAINER - P&ID PRIMARY RO TRAIN 2 CONTAINER - P&ID	X
55	O-14024-C01-0411	INTERSTAGE BOOSTER PUMP - P&ID	X
56	O-14024-C01-0420 O-14024-C01-0421	THIRD STAGE BOOSTER POINT - P&ID	X
57	O-14024-C01-0421	RO CIP SYSTEM - P&ID	X
58	O-14024-C01-0800-1	DOSING SKIDS - SINGLE PUMP SKID - P&ID	×
58 59	O-14024-C01-0800-1 O-14024-C01-0800-2	DOSING SKIDS - SINGLE PUMP SKID - P&ID DOSING SKIDS - SINGLE PUMP SKID - P&ID	X
59 60	O-14024-C01-0800-2 O-14024-C01-0810	CHEMICAL TREATMENT BUILDING - P&ID	X X
60 61	O-14024-C01-0810 O-14024-C01-0950	AIR COMPRESSOR SYSTEM - AIR SCOUT & MIT AS SEPARATE LINES - P&ID	X
62	O-14024-C01-0950 O-14024-C01-0990	UF BACKPULSE SYSTEM - P&ID	X X
	0-14024-C01-0990 IPPLY P&IDS	OF BACKFULDE STOTEIVI - PAID	Х
63	TYPICAL	P&ID - UV SYSTEM OVERVIEW	х
64	TYPICAL	P&ID - UV	X
٥.			^

| DESIGNED BY: E.Y. | DRAWN BY: O.N. | SHEET CHK'D BY: CROSS CHK'D BY: CROSS CHK'D BY: APPROVED BY: APPROVED BY: DATE: JULY 2014

WARNING
0 1/2" 1
IF THIS BAR SCAL
DOES NOT MEASUI
1" THIS DWC HAS
BEEN REDUCED
SCALE ACCORDING








CAMBRIA EMERGENCY WATER SUPPLY PROJECT CAMBRIA COMMUNITY SERVICE DISTRICT

TITLE SHEET AND SHEET INDEX

PROJECT NO. 138760-104133 FILE NAME:

G-01



FLOW BALANCE

AUTOMATIC STRAINER RECOVERY 99%
MF RECOVERY 92%
OVERALL RO RECOVERY 92%
CIP WASTE 0.5%

FLOW STREAM	AWTP FEED	MF FEED	AUTOMATIC STRAINER WASTE	MF FILTRATE	MF BACKWASH WASTE (NOTE 1)	MF AND AUTOMATIC STRAINER COMBINED WASTE	MF BACKWASH FEED (NOTE 1)	COMBINED RO FEED	PRIMARY RO 1 FEED	PRIMARY RO 1 PERMEATE	PRIMARY RO 1 CONCENTRATE	PRIMARY RO 2 FEED	PRIMARY RO 2 PERMEATE	PRIMARY RO 2 CONCENTRATE	THIRD STAGE RO FEED	THIRD STAGE RO PERMEATE	COMBINED RO PERMEATE	THIRD STAGE RO CONCENTRATE	PRODUCT WATER TO RECHARGE INJECTION WELL (RIW)	MF FILTRATE TO SAN SIMEON CREEK LAGOON	MF CIP FEED (NOTE 1.)	RO CIP FEED (NOTE 1)	MF CIP WASTE (NOTE 1)	RO CIP WASTE (NOTE 1)
FLOW STREAM ID	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
Average Flow (GPM)	691	684	7	629	55	62	55	529	265	212	53	265	212	53	106	64	487	42	484	100	2	1	2	1
Pressure (psi)	40	30	5	5	5	5	30	30	122	15	115	122	15	115	215	15	15	20	30	30	20	20	20	20
TDS (mg/L)	1374	1374	1374	1374	-	1374	1374	1374	1366	101	6756	1366	101	6756	6756	1108	222	14529	222	1374	-	-	1	-

CHEMICAL	AQUEOUS AMMONIA	SODIUM HYPOCHLORITE	SULFURIC ACID	THRESHOLD INHIBITOR	HYDROGEN PEROXIDE	SODIUM HYPOCHLORITE	CALCIUM CHLORIDE	SODIUM HYDROXIDE
CHEMICAL STREAM ID	Α	В	С	D	E	F	G	Н
Bulk Chemical Concentration	19.00%	12.50%	93.00%	100.00%	27.00%	12.50%	34.70%	25.00%
Chemical Dose, Max	1.5 mg/L	6.0 mg/L	45 mg/L	3.0 mg/L	5.0 mg/L	19 mg/L	40 mg/L	50 mg/L
Dosing Rate, Max	8.5 gpd	39 gpd	21 gpd	0.9 gpd	12 gpd	87 gpd	60 gpd	112 gpd

NOTES

- INTERMITTENT FLOW
- 2. ALL THE CHEMICAL DOSING SKIDS EXEPT THRESHOLD INHIBITOR WILL BE INSTALLED IN CONTAINER 5 (NOT SHOWN). THRESHOLD INHIBITOR DOSING SKIDS WILL BE INSTALLED IN CONTAINER 2 AND CONTAINER 3.
- 3. MAIN CONTROL ROOM AND OFFICE SPACE WILL BE SUPPLIED IN CONTINER 6 (NOT SHOWN).
- 4. RO FLOW CONDITIONS ARE BASED ON AN AVERAGE MEMBRANE AGE OF 3 YEARS.

'n							
Z I						DESIGNED BY:	Г
N N						DRAWN BY: RH	
2						SHEET CHK'D BY:	l
<u>+</u>						CROSS CHK'D BY:	l
ب						APPROVED BY:	l
S C	REV. NO.	DATE	DRWN	CHKD	REMARKS	DATE: JUNE, 2014	

WARNING
0 1/2" 1"
IF THIS BAR SCALE DOES NOT MEASURE
1" THIS DWG HAS BEEN REDUCED
SCALE ACCORDINGLY









CAMBRIA EMERGENCY WATER SUPPLY PROJECT CAMBRIA COMMUNITY SERVICE DISTRICT


PROCESS FLOW DIAGRAM


PROJECT NO. 138760-104133
FILE NAME:
SHEET NO.


P-01













NOT FOR CONSTRUCTION





IF THIS BAR SCALE DOES NOT MEASURE 1" THIS DWG HAS BEEN REDUCED SCALE ACCORDINGLY


PPROVED BY:_


REMARKS





CAMBRIA COMMUNITY SERVICE DISTRICT





 ∇

 $\overline{\mathsf{W}}$

 $\overline{\mathbb{W}}$

\F/

⟨G∕

 $\overline{\mathsf{A}}$ GENERAL STRUCTURAL NOTES DESIGN CRITERIA: CODES CBC-2013 (CALIFORNIA BUILDING CODE 2013) ACI 318-11 (BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE) LIVE LOADS: PROCESS FLOORS AND SLABS 200 PSF (NON-REDUCIBLE) RISK CATEGORY IV WIND DESIGN DATA 115 MPH (ULTIMATE) BASIC WIND SPEED, Vult EXPOSURE CATEGORY SEISMIC DESIGN DATA: MAPPED SPECTRAL RESPONSE ACCELERATIONS SPECTRAL RESPONSE COEFFICIENTS Sds = 1.060gSd1 = 0.601gSHORT PERIOD ONE SECOND PERIOD
SEISMIC DESIGN CATEGORY
SEISMIC IMPORTANCE FACTOR, le 1.5 GROUND SNOW LOAD Pa 0 PSF SEISMIC REQUIREMENTS - NON-STRUCTURAL COMPONENTS: IN ACCORDANCE WITH THE REQUIREMENTS OF CBC AND BY REFERENCE ASCE 7-10. ALL MECHANICAL, ELECTRICAL AND NON-STRUCTURAL COMPONENTS AND EQUIPMENT AND ANCHORAGES FOR RISK CATEGORY IV AREAS SHALL BE DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION 13 OF ASCE 7 WITH A COMPONENT IMPORTANCE FACTOR FOR THIS PURPOSE ALL COMPONENTS AND EQUIPMENT SHALL BE CONSIDERED TO HAVE THE SAME SEISMIC DESIGN CATEGORY AS THAT OF THE STRUCTURE THEY OCCUPY. FOUNDATIONS ARE DESIGNED FOR ALLOWABLE SOIL PRESSURE OF 600 PSF. ALL EXTERIOR FOUNDATIONS SHALL EXTEND TO A DEPTH = 18". SEE CIVIL SITE PLANS FOR STRUCTURE LOCATION COORDINATES.

ALL STRUCTURAL DRAWINGS SHALL BE USED IN CONJUNCTION WITH THE OTHER PROJECT DRAWINGS AND SPECIFICATIONS.

STANDARD DETAILS SHALL BE USED AT ALL APPLICABLE LOCATIONS, UNLESS NOTED

FIELD VERIFY ALL EXISTING DIMENSIONS PRIOR TO CONSTRUCTION

WRITTEN DIMENSIONS SHALL TAKE PRECEDENCE OVER SCALED SIZES.

CONSTRUCTION NOTES:

PRIOR TO INSTALLATION OF EQUIPMENT, COORDINATE AND CONFIRM THE ANCHORAGE REQUIREMENTS WITH THE MANUFACTURER. THE ANCHORAGE SYSTEM SHALL NOT DAMAGE

CONTRACTOR SHALL VERIFY ALL DIMENSIONS IN THE FIELD. THE PROJECT MANAGER SHALL BE NOTIFIED OF ANY DISCREPANCY BETWEEN DRAWINGS IMMEDIATELY UPON DISCOVERY.

CONCRETE ANCHORS AND DOWELS:

CONTRACTOR SHALL LOCATE EXISTING REBAR USING NON-DESTRUCTIVE METHODS PRIOR TO DRILLING HOLES FOR ADHESIVE AND EXPANSION ANCHORS. ADJUST SPACING OF ANCHORS TO MISS REINFORCING A MAXIMUM OF 1 1/2" FROM DETAILED LOCATIONS.

ADHESIVE FOR EMBEDED DOWELS AND ANCHORS SHALL BE HILTI HIT-RE 500-SD (ICC EVALUATION REPORT 2322), OR APPROVED EQUAL. DRILLED HOLES SHALL BE SIZED ACCORDING TO MANUFACTURER'S RECOMMENDATIONS.

EXPANSION ANCHORS SHALL BE HILTI KWIK BOLT TZ, (ICC EVALUATION REPORT 1917), OR

ICC REPORTS SHALL STATE THAT ANCHORS ARE COMPLIANT WITH THE 2012 IBC AND CAN BE USED TO RESIST EARTHQUAKE LOADS IN CRACKED, NORMAL-WEIGHT CONCRETE.

CAST-IN-PLACE CONCRETE:

REINFORCED CONCRETE SHALL CONFORM TO ACI 318.

REINFORCING STEEL FABRICATION SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE CRSI MANUAL OF STANDARD PRACTICE.

CONCRETE WORK SHALL CONFORM TO ACI 301 (SPECIFICATIONS FOR STRUCTURAL

MINIMUM CONCRETE COVER SHALL BE TO NEAREST EXPOSED SURFACE.

ALL EXPOSED CORNERS OF CONCRETE SHALL HAVE 3/4" CHAMFER, UNLESS OTHERWISE

 ∇

WALL REINFORCEMENT AT CORNERS OR JUNCTIONS OF WALLS SHALL BE CONTINUOUS, LAPPED, OR TERMINATED IN AN ACI STANDARD 90 DEGREE STANDARD HOOK DETAIL LAP SPLICES SHALL CONFORM WITH THE TABLE ON THIS SHEET.

UNLESS OTHERWISE INDICATED ON THE DRAWINGS, BARS SHALL BE DOWELED. DOWELS SHALL BE THE SAME SIZE AND SPACING AS THE REINFORCEMENT WHICH IS SPLICED TO THE DOWELS UNLESS OTHERWISE NOTED.

SLABS. BEAMS. AND COLUMN REINFORCING BARS SHALL HAVE A MINIMUM EXTENSION OR ANCHORAGE INTO SUPPORTS IN ACCORDANCE WITH ACI 318.

STIRRUP SUPPORT BARS SHALL BE PROVIDED AS REQUIRED TO SECURE TOP BARS

UNLESS OTHERWISE INDICATED ON THE DRAWINGS, CONCRETE COVER OVER #11 AND SMALLER REINF BARS SHALL BE AS FOLLOWS:

```
FORMED CONCRETE SURFACES AND UNFORMED TOP SURFACES
 LOCATED OVER FLUIDS......
BEAMS AND COLUMNS:
 FORMED CONCRETE SURFACES FOR DRY CONDITIONS:
    STIRRUPS, SPIRALS AND TIES ...
    PRINCIPAL REINFORCEMENT..
 FORMED CONCRETE SURFACES EXPOSED TO WEATHER, IN CONTACT WITH SOIL OR FLUIDS, OR BEAMS LOCATED OVER FLUIDS:
    PRINCIPAL REINFORCEMENT.
 FORMED CONCRETE SURFACES FOR DRY CONDITIONS......FORMED CONCRETE SURFACES EXPOSED TO WEATHER OR IN
CONTACT WITH SOIL OR FLUIDS.
FOOTINGS AND SLABS ON GRADE:
 FORMED CONCRETE SURFACES.
  AT UNFORMED CONCRETE SURFACES CAST AGAINST THE SOIL OR
 CONCRETE WORK MATS.
```

CONSTRUCTION JOINTS SHALL NOT BE PLACED AT LOCATIONS OTHER THAN THOSE SHOWN ON THE DRAWINGS WITHOUT THE PRIOR WRITTEN APPROVAL OF THE ENGINEER.

TYPICAL STRUCTURAL MATERIALS:

SEE PROJECT SPECIFICATIONS AND NOTES ON DRAWINGS FOR INDIVIDUAL STRUCTURES FOR DETAILED OR SPECIAL REQUIREMENTS.

ONCRETE FILL, DUCT ENCASEMENT, WHERE NOTED: CLASS A (f'c = 2500 PSI) STRUCTURAL CONCRETE; $W/C \le 0.54 \text{ CLASS B } (f'c = 3000 \text{ PSI})$ REINFORCING STEEL: ASTM A615, GRADE 60 (Fy = 60,000 PSI) REINFORCING STEEL (WELDABLE): ASTM A706, GRADE 60 (Fy = 60,000 PSI) CRIFTING ASTM ACTU CASE OF THE PROPERTY OF THE PR

CEMENT: ASTM C150, TYPE II AIR ENTRAINMENT: 3.5 TO 5.0 PERCENT

STRUCTURAL STEEL

SHAPES – W AND WT: ASTM A992 (Fy = 50 KSI) SHAPES – S, M, HP, C, MC, L, PLATE AND BAR: ASTM A36 (Fy = 36 KSI) HOLLOW STRUCTURAL SECTIONS: ROUND: ASTM A500, GRADE B (Fy = 42 KSI) SQUARE AND RECTANGULAR: ASTM A500, GRADE B (Fy = 46 KSI) ANCHOR RODS: ASTM F1554, ¾"ø MINIMUM UNO (Fy = 36 KSI)

WELDING ELECTRODES: E70XX (Ft = 70 KSI)
ASSEMBLY BOLTS: HIGH STRENGTH ASTM A325-N

SPECIAL INSPECTION REQUIREMENTS

SPECIAL INSPECTIONS SHALL BE CONDUCTED IN ACCORDANCE WITH THE REQUIREMENTS SET FORTH IN CHAPTER 17 OF THE CALIFORNIA BUILDING CODE.

IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 17 OF THE BUILDING CODE, THE PERMIT APPLICANT WILL PROVIDE QUALIFIED PERSONNEL TO PERFORM THE FOLLOWING SPECIAL INSPECTIONS AND SHALL FURNISH INSPECTION REPORTS FROM THE SPECIAL INSPECTOR TO THE ENGINEER AND BUILDING OFFICIAL. THIS DOES NOT RELIEVE THE CONTRACTOR OF ANY RESPONSIBILITY TO PERFORM THE WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS. THE CONTRACTOR SHALL NOTIFY THE INSPECTOR 24 HOURS IN ADVANCE OF ALL INSPECTIONS

SECONDARY CONTAINMENT SHALL RECEIVE SPECIAL INSPECTION: CONCRETE CONSTRUCTION (1704.4) SOILS (1704.7)

ABBREVIATIONS: NUMBER

INTERIOR ANCHOR BOLT INVERT ABOVE ADDITIONAL AGGREGATE KNOCKOUT LONG LEG HORIZONTAL ALTERNATE (ING) LONG LEG VERTICAL APPROXIMATELY
ARCHITECT (URAL) (URE)
BACK TO BACK LINTEL
LOCATION/LOCATED
LONGITUDINAL BEV BLK BLKG BEVEL (ED) LOW POINT LIGHTWEIGHT B.O. BOT BRG C TO C CIRC CJ CL OR Q MASONRY MATERIAL воттом MAX MB MCJ MECH MAXIMUM CENTER TO CENTER MACHINE BOLTS MASONRY CONTROL JOINT CIRCUMFERENTIAL CONSTRUCTION JOINT MECHANICAL CENTERLINE CLEAR MISCELLANEOUS CONCRETE MASONRY UNITS CMU COL COMP CONC CONN CONT CPLG CRS CSK CTG CTR MASONRY OPENING NEAR FACE NON-SHRINK GROUT CONCRETE NOT TO SCALE
ON CENTER OR OCCUPANCY CATEGORY CONNECTION CONTINUOUS COUPLING OUTSIDE DIAMETER OUTSIDE FACE OPENING OPPOSITE OF OPNG OPP OPP HD OPT PCF PCJ PJF COURSE (S) COUNTERSIN COATING CENTER (ED) OPPOSITE HAND OPTION (AL)
POUNDS PER CUBIC FOOT
PARTIAL CONTRACTION JOINT
PREMOLDED JOINT FILLER d DET PL OR PLYWD PREFAB PROJ PSF PSI PVMT PLATE PLYWOOD
PREFABRICATED
PROJECTION
POUNDS PER SQUARE FOOT DIRECTION DEAD LOAD POUNDS PER SQUARE INCH PAVEMENT EXPANSION BOLT EACH FACE RAD RC REF REINF RADIUS REINFORCED CONCRETE REFERENCE/REFER REINFORCE (D, ING) REQUIRED ELEVATION ELEC ELECTRIC (AL) EMBED EQ EQPT ES EW EMBEDMEN EQUAL (LY) REQD ROUGH OPENING EXPANSION ANCHOR EXPANSION JOINT SCHED SCJ SECT SFR SCHEDULE SLAB CONTROL JOINT **FXTFRIOR** Section Synthetic fiber reinforced CONCRETE COMPRESSION STRESS
MASONRY PRISM STRESS
FABRICATE (OR) (ED) SIM SPACE (S) (ED)
SPECIFICATION/SPECIFIED FLOOR DRAIN FOUNDATION FAR FACE SQ SST STAINLESS STEEL FHMS STD STIF STIR SYM FLATHEAD MACHINE SCREW FLATHEAD WOOD SCREW STIFFENER STIRRUP (S) SYMMETRICAL FIBERGLASS REINFORCED PLASTIC TREAD (S)
TOP AND BOTTOM
TOP FACE FEET/FOOT FOOTING/FITTING GAGE FTG GA GALV GI THD TOC TOW THREADED GALVANIZED TOP OF CONCRETE GALVANIZED IRON GLASS BLOCK TRANSVERSE TOP OF SLAB TRNSV TSL TYP UNO VB VERT

G/

ABBREVIATION NOTES:

HIGH POINT

ABBREVIATIONS AND DESIGNATIONS FOR STEEL MEMBERS MAY BE FOUND IN THE CURRENT MANUAL OF STEEL CONSTRUCTION BY AISC.

ABBREVIATIONS OF TECHNICAL SOCIETIES AND TRADE ASSOCIATIONS MAY BE FOUND IN THE SPECIFICATIONS.

WELDING SYMBOLS AND ABBREVIATIONS MAY BE FOUND IN AWS 2.4.

HOLLOW STRUCTURAL SECTION
HEATING, VENTILATING & AIR CONDITIONING

STRUCTURAL LEGEND AND SYMBOLS:

HEADED ANCHOR STUD

IN ACCORDANCE WITH

INDICATES EQUIPMENT PAD PER DETAILS J OR K ON SHEET S-200-003. COORDINATE SIZE WITH EQUIPMENT REQUIREMENTS. Œ

HYDROPHILIC (EXPANSIVE) WATERSTOP GRATING SPAN DIRECTION



UNDISTURBED CONCRETE

STEEL

CONCRETE

GRATING

SAND CHECKERED

UNLESS NOTED OTHERWISE VAPOR BARRIER

VERTICAL WIDE FLANGE

WITHOUT

WATERSTOR

WORKING POINT

WELDED WIRE FABRIC

 $\overline{\mathbb{W}}$

INSIDE DIAMETER

INSIDE FACE

GROUT SHALE PROJECT NO. XXXXX-XXXXXX FILE NAME: S-01.dw

PRELIMINARY NOT FOR CONSTRUCTION

07/03/2014











CAMBRIA EMERGENCY WATER SUPPLY PROJECT CAMBRIA COMMUNITY SERVICE DISTRICT

STRUCTURAL GENERAL NOTES

SHEET NO. S-01


NOTES:
1 "TOP" BARS IS HORIZONTAL REINFORCEMENT PLACED SO THAT MORE THAN 12" OF FRESH CONCRETE IS CAST IN THE MEMBER BELOW THE DEVELOPMENT LENGTH OR SPLICE.

CLEAR SPACING OF BARS BEING DEVELOPED OR SPLICED SHALL A) NOT BE LESS THAN d_b , HAVE CLEAR COVER NOT LESS THAN d_b , AND STIRRUPS OR TIES THROUGHOUT L_d NOT LESS THAN THE CODE MINIMUM OR; B) CLEAR SPACING OF BARS WHERE d_b =DIAMETER OF REINFORCING BAR AND L_d =DEVELOPMENT LENGTH.

FOR SPECIAL SPLICE REQUIREMENTS FOR COLUMNS AND END BEARING SPLICES IN COMPRESSION SEE ACI 318

TABLE IS BASED ON f'c=4000 PSI and fy=60,000 PSI. LAP SPLICE AND DEVELOPMENT LENGTHS SHALL BE INCREASED FOR LOWER CONCRETE COMPRESSIVE STRENGTH AS FOLLOWS:


OLLO		MULTIPLIER				MULTIPLIE
2500	PSI	1.27	f'c	3500	PSI	1.07
3000	PSI	1.16	f'c	4500	PSI	0.94



MAX OFFSET BEND 90° STD HOOK 180° STD HOOK


D=6d FOR #3 TO #8 D=8d FOR #9 TO #11 D=12d FOR #14 AND #18

PRINCIPAL REINFORCING



MIN D=1 1/2" FOR #3 MIN D=2" FOR #4 MIN D=2 1/2" FOR #5

STIRRUPS AND TIES



REINFORCEMENT AT CIRCULAR OPENINGS GREATER THAN 12"

DETAIL

AREA EQUAL TO 50%

OF INTERRUPTED BARS EACH SIDE

WHERE OPENING IS

WITHIN 4'-0" OF BASE SLAB PROVIDE MATCHING DOWELS FOR ADDITIONAL

INTERRUPTED -AREA EQUAL TO 50% OF INTERRUPTED BARS EACH SIDE -2-#4x4'-0" @ 4" WHERE OPENING IS WITHIN 4'-0" OF BASE SLAB PROVIDE MATCHING DOWELS FOR ADDITIONAL CLASS "B"
TENSION LAP

 $\overline{\mathbb{W}}$


REINFORCEMENT AT RECTANGULAR OPENINGS GREATER THAN 12"

DETAIL D` NTS






 ∇



DETAIL

 $\overline{\mathbb{W}}$





2 NO CHAMFER REQUIRED WHERE FLUSH EXTERIOR CMU OR BRICK MASONRY ABOVE.

STANDARD HOOK AND LAP SPLICE IN CONCRETE

3/4"


DETAIL





NOTE:
1 PADS FOR PUBLIC UTILITY EQUIPMENT SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE APPROPRIATE AGENCIES REQUIREMENTS.






INTERRUPTED -

CLASS "B"





DIMENSIONS OF PAD AS REQUIRED TO SUIT EQUIPMENT (4" MIN UNLESS PAD IS CAST INTEGRALLY WITH SLAB).

> **EQUIPMENT PAD DETAIL**

PRELIMINARY NOT FOR CONSTRUCTION

07/03/2014












CAMBRIA EMERGENCY WATER SUPPLY PROJECT CAMBRIA COMMUNITY SERVICE DISTRICT


STRUCTURAL STANDARD DETAILS


PROJECT NO. XXXXX-XXXXXX FILE NAME: S-02.dw SHEET NO. S-02


ゔ


1" THIS DWG HAS BEEN REDUCED SCALE ACCORDINGLY











PRELIMINARY NOT FOR CONSTRUCTION

07/03/2014

OPERATOR INTERFACE-

REMOTE ON/OFF_ SELECTOR

- NOTES:

 : MAXIMUM OPERATING PRESSURE TO BE 65 psi [4.5 BAR].

 : MAXIMUM OPERATING PRESSURE TO BE 65 psi [4.5 BAR].

 : INTERCONNECTING CABLE LENGTH TO BE 12 FT. [3658mm] FROM CONDUIT CONNECTOR

 ON UV CHAMBER END CAP TO CONDUIT CONNECTOR ON PDC.

 :INLET/OUTLET GASKETS AND HARDWARE TO BE SUPPLIED BY CUSTOMER.

 :INLET/OUTLET GASKETS AND HARDWARE TO BE SUPPLIED BY CUSTOMER.

 :INLET/OUTLET AWMA C207 CLASS D FLANGE.

 :INLET/OUTLET AWMA C207 CLASS D FLANGE.

 :HAZI EXCHANGER SHOWN FOR CLARITY.

 : 72AL75 CHAMBER WEIGHT DRY 2100 lbs. [953 kg.] / WET 3700 lbs. [1678 kg.]

 : VO CHAMBER WEIGHT DRY 2100 lbs. [953 kg.] / WET 3700 lbs. [1678 kg.]

 : VO CHAMBER WEIGHT DRY 2100 lbs. [953 kg.] / WET 3700 lbs. [1678 kg.]

 : VO CHAMBER MATERIAL TO BE 316 STAINLESS STEEL

 : POWER DISTRIBUTION CENTER TO BE PAINTED MILD STEEL (STANDARD) 304 SST (OPTIONAL).

 : SCC MATERIAL TO BE MILD STEEL (STANDARD) OR 304 SST (OPTIONAL).


 : SCC MATERIAL TO BE MILD STEEL (STANDARD) OR 305 SST (OPTIONAL).


 : SCC TOPO WITHING MAXIMUM DISTANCE OF 1000 ft. [304.8m] REQUIRING A FIBER


 OPTIC CABLING ALL OTHER WIRING HAS A MAXIMUM DISTANCE OF 500 ft. [91.4m].


 INDICATES DIMENSIONS ARE SUBJECT TO CHANGE BASED ON PROJECT SPECIFIC REQUIREMENTS.


NLET / OUTLET PIPE SIZE (SS)	DIM A	DIM B
8	1'-4" [402]	5'-11" [1805]
12	1'-6" [454]	5'-9 " [1753]
16	1'–7 <mark>2</mark> " [496]	5'-7 2" [1711]
20	1'–9 <mark>2</mark> " [546]	5'-5½" [1660]
































TROJANÜŸ


CONFIDENTIALITY NOTICE
Copyright 2012 by Trojon Technologies. All rights reserved
No part of this document may be reproduced, stored in
retrieval system, or transmitted in any form, without the
written permission of Troj


UV **GENERAL ARRANGEMENT**














\C/

 \overline{A}

GENERAL NOTES

- THIS LEGEND APPLIES TO P&IDS ONLY AND MAY DIFFER FROM LEGENDS FOR OTHER SHEETS.
- 2. IN GENERAL THIS LEGEND SHEET AND THE P&IDS ARE BASED ON INTERNATIONAL SOCIETY OF AUTOMATION (ISA)
 STANDARDS FOR PRACTICES FOR INSTRUMENTATION. SOME
 MODIFICATIONS, ADDITIONS AND ALTERATIONS HAVE BEEN MADE AS REQUIRED TO ACCOMODATE PROJECT REQUIREMENTS

 \overline{H}

- SOME PROCESS ITEMS, SUCH AS EQUIPMENT ISOLATION VALVES, BYPASS LINES, ETC., WHICH ARE NOT CRITICAL FOR AN UNDERSTANDING OF THE INSTRUMENTATION FUNCTIONS ARE NOT SHOWN ON THE P&IDS.
- SEE ELECTRICAL AND MECHANICAL SHEETS AND SPECIFICATIONS FOR ADDITIONAL CONTROL AND INTERLOCK REQUIREMENTS.
- LIGHTER WEIGHT LINES, SHOWN AS _____, INDICATE EQUIPMENT, INSTRUMENTS OR PIPING THAT ARE EXISTING. WEIGHTED LINES, SHOWN AS _____, OR HEAVIER ____, INDICATE EQUIPMENT, INSTRUMENTS OR PIPING THAT ARE

PRELIMINARY NOT FOR CONSTRUCTION

\F/

TELEPHONE SIGNAL

SIGNAL (GUIDED)

PNEUMATIC SIGNAL

SOFTWARE I/O

FIBER-OPTIC CABLE

ELECTROMAGNETIC OR SONIC SIGNAL (UNGUIDED)

VENDOR SUPPLIED CABLE

CAT-6 COMMUNICATION CABLE


LOCATION NORMALLY NOT ACCESSIBLE TO OPERATOR

GENERAL INSTRUMENT OR FUNCTION SYMBOLS

INSTRUMENTS SHARING COMMON HOUSING


PILOT LIGHT


I/O SIGNALS





PROCESS AND INSTRUMENTATION LEGEND, SYMBOLS, AND **ABBREVIATIONS**


PROJECT NO. 138760-104133 FILE NAME: SHEET NO. 1-1





















PRELIMINARY NOT FOR CONSTRUCTION

07/03/2014



© 2014 CDM SMITH ALL RIGHTS RESERVED. REUSE OF DOCUMENTS: THESE DOCUMENTS

REV. DATE DRWN CHKD

WARNING
0 1/2" 1"
IF THIS BAR SCALE
DOES NOT MEASURE
1" THIS DWG HAS
BEEN REDUCED
SCALE ACCORDINGLY

H.NGUYEN

J. ISIDORO

JUNE, 2014

DESIGNED BY:__

SHEET CHK'D BY:_

CROSS CHK'D BY:_

DRAWN BY:__

REMARKS

CDM Smith

111 Academy Way, Suite 150 Irvine, California 92617
Telt (949) 752-452






CAMBRIA EMERGENCY
WATER SUPPLY PROJECT
CAMBRIA COMMUNITY SERVICE DISTRICT

PROCESS AND INSTRUMENTATION DIAGRAM PRODUCT WATER TANK, PUMP STATION AND RIW INJECTION

PROJECT NO. 138760-104133
FILE NAME: I-10.DWG
SHEET NO.
I-10


 \forall



PRELIMINARY NOT FOR CONSTRUCTION 07/03/2014

NOTE:

 THE SUBMERSIBLE PUMPS WILL BE ANCHORED AT FLOATING STRUCTURE



WARNING
0 1/2" 1"
IF THIS BAR SCALE
DOES NOT MEASURE
1" THIS DWG HAS

CDM Smith 111 Academy Way, Suite 150 Irvine, California 92617 Tel: (949) 752-5452





CAMBRIA EMERGENCY WATER SUPPLY PROJECT CAMBRIA COMMUNITY SERVICE DISTRICT

PROCESS AND INSTRUMENTATION DIAGRAM BRINE EVAPORATION SYSTEM

PROJECT NO. 138760-104133
FILE NAME: I-12.DWC
SHEET NO.


I-12


NOT FOR CONSTRUCTION


PRELIMINARY NOT FOR CONSTRUCTION


07/03/2014


VENDOR PACKAGE H2OI SUPPLY

















PRELIMINARY NOT FOR CONSTRUCTION

07/03/2014

THE INFORMATION, SPECIFICATIONS AND DATA SHOWN ON THIS PRINT ARE FURNISHED BY AND ARE TO REMAIN HE PROPERTY OF h₂o Innovation. THE ACCEPTOR WARRANTS THAT NO USE WILL BE MADE

OF THE SAME EXCEPT TO FACILITATE THE INSTALLATION, MAINTENANCE AND OPERATION OF THE EQUIPMENT REPRESENTED BY SAID PRINT.

			DRAWING REVISION		•		·	
	REV	DATE	REVISION DESCRIPTION	DRAWN	CHKD	ENG	APPVD	
	A	12-14	PRELIMINARY	M.C	M.C	M.C		
=								
۷,								innovation


CAMBRIA COMMUNITY SERVICE DISTRICT EMERGENCY SUPPLY PROJECT

PRIMARY RO TRAIN 1
PROCESS & INSTRUMENTATION
DIAGRAM
au a

FILE:	O-14024-C01-0410
DATE:	7/9/12
SHEET	: 1 OF 1
SCALE	: N.T.S.
	REVISION

Α

HECKED: M.B O-14024-C01-0410



PRELIMINARY NOT FOR CONSTRUCTION

07/03/2014

NOTE:
THE INFORMATION, SPECIFICATIONS AND DATA SHOWN
ON THIS PRINT ARE FURNISHED BY AND ARE TO REMAIN
THE PROPERTY OF h₂o Innovation.
THE ACCEPTOR WARRANTS THAT NO USE WILL BE MADE
OF THE SAME EXCEPT TO FACILITATE THE INSTALLATION,
MAINTENANCE AND OPERATION OF THE EQUIPMENT


$\overline{}$									_
WN			DRAWING REVISION						
IAIN	REV	DATE	REVISION DESCRIPTION	DRAWN	CHKD	ENG	APPVD		
	A	12-6	PRELIMINARY	M.C	M.C	M.C			
ADE									
IADE TION.									
11014,								innovation	


CAMBRIA COMMUNITY SERVICES
DISTRICT EMERGENCY
SUPPLY PROJECT

PRIMARY RO TRAIN 2	
PROCESS & INSTRUMENTATION	
DIAGRAM	

FILE:	O-14024-C01-411
DATE:	2014-06-12
SHEET:	
SCALE:	N.T.S.
	DEVICION


RAWN BY:	RMG	CHECKED:	GJM	DRAWING NUMBER:
NGINEER:	RMG	APPROVED:		O-14024-C01-C01-0411





PRELIMINARY NOT FOR CONSTRUCTION

07/03/2014



NOTE: THE INFORMATION, SPECIFICATIONS AND DATA SHOWN								
ON THIS PRINT ARE FURNISHED BY AND ARE TO REMAIN	REV	DATE	REVISION DESCRIPTION	DRAWN	CHKD	ENG	APPVD	N
THE PROPERTY OF h ₂ o Innovation.	A	7/9/12	PRELIMINARY	M.C	M.B	M.B		
THE ACCEPTOR WARRANTO THAT MO HOE WILL BE MADE								
THE ACCEPTOR WARRANTS THAT NO USE WILL BE MADE OF THE SAME EXCEPT TO FACILITATE THE INSTALLATION.								
MAINTENANCE AND OPERATION OF THE EQUIPMENT								innovation
REPRESENTED BY SAID PRINT.								

CAMBRIA COMMUNITY SERVICES **EMERGENCY WATER** SUPPLY PROJECT

TLE:				FILE:	O-14024
	DATE:				
PROCE	ESS & INS	MENTATION	SHEET:	1 C	
	DIAG	BRAM		SCALE:	N. ⁻
RAWN BY: RMG	CHECKED:	GJM	DRAWING NUMBER:		
NGINEER: RMG	APPROVED:		P12069-	C01-12	<u> </u>

INGINEER: RMG

